

K318i (windage left)

ULTRASHORT PRECISION TOOL



The K318i means optical and mechanical perfection packed into an ultrashort design. With precise illuminated reticles in 1 st focal plane, sharply defined throughout the entire magnification range and the unique TWIST GUARD windage.

PRODUCT HIGHLIGHTS

- Ultrashort and lightweight riflescope for demanding shooters
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Wide field of view and exceptional high contrast image
- Innovative TWIST GUARD windage (patented)
- Parallax wheel integrated into the elevation turret (patented) (25 m to ∞)
- Precise illuminated reticles in 1 st focal plane

TECHNICAL DATA

Magnification:	3.5 - 18
Eye relief:	3.62 in
Field of view:	27.8 - 5.5 in/100 yds
Diopter compensation:	+2.5 / -3.5 dpt
Twilight factor (DIN 58388):	13.2 - 30.0
Impact correction per click:	.1 MRAD ¼ MOA
Adjustment range (E/W):	106.0 / 72.0 in/100 yds 30.0 / 20.0 MILS 102.0 / 69.0 MOA
Parallax adjustment:	25 m till ∞
Tube diameter:	34 mm / 1.34 in
Length:	12.3 in
Weight:	33.2 oz
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years

FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction CCW



Zero Stop



TWIST GUARD windage




Windage left or right




MOA or MIL


RETICLES / SUBTENSIONS




MSR/Ki



MOAK



SKMR3



TREMOR 3